

PRO-SPRAY	APLICATII	MODELE
ASPERSOR ESCAMOTABIL STATIC	rezidential	shrub, 10cm, 15cm, 30cm

CARACTERISTICI

- Modele : ridicare 0cm, 10cm, 15cm sau 30cm
- Racordare prin lateral valabil pentru modelele cu ridicare de 15 si 30cm
- Compatibil cu toate duzele cu filet interior

CARACTERISTICI FUNCTIONARE

Presiunea recomandata : $1.0 \div 5\text{bar}$; $100 \div 500\text{kPa}$

DIMENSIUNI

Inaltimea totala :

- Modelul shrub (0cm) : 4cm
- Modelul cu ridicare 10cm : 15.5cm
- Modelul cu ridicare 15cm : 22.5cm
- Modelul cu ridicare 30cm :

Diametru expus : 3cm

Sistem de prindere : $\frac{1}{2}$ " Fi



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

4A

Raza : 1.2m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
			Bar	m	m ³ /h	l/min
45°	1.0	0.9	0.02	0.33	162	187
	1.5	0.9	0.02	0.33	202	234
	2.0	1.2	0.02	0.33	133	154
	2.1	1.2	0.02	0.33	137	158
	2.5	1.2	0.03	0.50	151	174
90°	1.0	0.9	0.03	0.50	162	187
	1.5	0.9	0.04	0.67	202	234
	2.0	1.2	0.05	0.83	133	154
	2.1	1.2	0.05	0.83	137	158
	2.5	1.2	0.05	0.83	151	174
120°	1.0	0.9	0.04	0.67	162	187
	1.5	0.9	0.05	0.83	202	234
	2.0	1.2	0.06	1.00	133	154
	2.1	1.2	0.07	1.17	137	158
	2.5	1.2	0.07	1.17	151	174
180°	1.0	0.9	0.07	1.17	162	187
	1.5	0.9	0.08	1.33	202	234
	2.0	1.2	0.1	1.67	133	154
	2.1	1.2	0.1	1.67	137	158
	2.5	1.2	0.11	1.83	151	174
240°	1.0	0.9	0.09	1.50	162	187
	1.5	0.9	0.11	1.83	202	234
	2.0	1.2	0.13	2.17	133	154
	2.1	1.2	0.13	2.17	137	158
	2.5	1.2	0.14	2.33	151	174
270°	1.0	0.9	0.1	1.67	162	187
	1.5	0.9	0.12	2.00	202	234
	2.0	1.2	0.14	2.33	133	154
	2.1	1.2	0.15	2.50	137	158
	2.5	1.2	0.16	2.67	151	174
360°	1.0	0.9	0.13	2.17	162	187
	1.5	0.9	0.16	2.67	202	234
	2.0	1.2	0.19	3.17	133	154
	2.1	1.2	0.2	3.33	137	158
	2.5	1.2	0.22	3.67	151	174

6A

Raza : 1.8m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
			Bar	m	m ³ /h	l/min
45°	1.0	1.5	0.02	0.33	79	91
	1.5	1.5	0.03	0.50	98	113
	2.0	1.8	0.03	0.50	80	92
	2.1	1.8	0.03	0.50	82	95
	2.5	1.8	0.04	0.67	90	104
90°	1.0	1.5	0.04	0.67	79	91
	1.5	1.5	0.06	1.00	98	113
	2.0	1.8	0.06	1.00	80	92
	2.1	1.8	0.07	1.17	82	95
	2.5	1.8	0.07	1.17	90	104
120°	1.0	1.5	0.06	1.00	79	91
	1.5	1.5	0.07	1.17	98	113
	2.0	1.8	0.09	1.50	80	92
	2.1	1.8	0.09	1.50	82	95
	2.5	1.8	0.1	1.67	90	104
180°	1.0	1.5	0.09	1.50	79	91
	1.5	1.5	0.11	1.83	98	113
	2.0	1.8	0.13	2.17	80	92
	2.1	1.8	0.13	2.17	82	95
	2.5	1.8	0.15	2.50	90	104
240°	1.0	1.5	0.12	2.00	79	91
	1.5	1.5	0.15	2.50	98	113
	2.0	1.8	0.17	2.83	80	92
	2.1	1.8	0.18	3.00	82	95
	2.5	1.8	0.19	3.17	90	104
270°	1.0	1.5	0.13	2.17	79	91
	1.5	1.5	0.17	2.83	98	113
	2.0	1.8	0.19	3.17	80	92
	2.1	1.8	0.2	3.33	82	95
	2.5	1.8	0.22	3.67	90	104
360°	1.0	1.5	0.18	3.00	79	91
	1.5	1.5	0.22	3.67	98	113
	2.0	1.8	0.26	4.33	80	92
	2.1	1.8	0.27	4.50	82	95
	2.5	1.8	0.29	4.83	90	104



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

8A

Raza : 2.4m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar	m	m ³ /h	l/min	□	Δ
45°	1.0	1.7	0.02	0.33	62	72
	1.5	2.1	0.03	0.50	51	59
	2.0	2.4	0.03	0.50	46	53
	2.1	2.7	0.03	0.50	37	43
	2.5	2.8	0.04	0.67	38	44
90°	1.0	1.7	0.04	0.67	62	72
	1.5	2.1	0.06	1.00	51	59
	2.0	2.4	0.07	1.17	46	53
	2.1	2.7	0.07	1.17	37	43
	2.5	2.8	0.07	1.17	38	44
120°	1.0	1.7	0.06	1.00	62	72
	1.5	2.1	0.07	1.17	51	59
	2.0	2.4	0.09	1.50	46	53
	2.1	2.7	0.09	1.50	37	43
	2.5	2.8	0.1	1.67	38	44
180°	1.0	1.7	0.09	1.50	62	72
	1.5	2.1	0.11	1.83	51	59
	2.0	2.4	0.13	2.17	46	53
	2.1	2.7	0.13	2.17	37	43
	2.5	2.8	0.15	2.50	38	44
240°	1.0	1.7	0.12	2.00	62	72
	1.5	2.1	0.15	2.50	51	59
	2.0	2.4	0.17	2.83	46	53
	2.1	2.7	0.18	3.00	37	43
	2.5	2.8	0.2	3.33	38	44
270°	1.0	1.7	0.13	2.17	62	72
	1.5	2.1	0.17	2.83	51	59
	2.0	2.4	0.2	3.33	46	53
	2.1	2.7	0.2	3.33	37	43
	2.5	2.8	0.22	3.67	38	44
360°	1.0	1.7	0.18	3.00	62	72
	1.5	2.1	0.22	3.67	51	59
	2.0	2.4	0.26	4.33	46	53
	2.1	2.7	0.27	4.50	37	43
	2.5	2.8	0.3	5.00	38	44

10A

Raza : 3m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar	m	m ³ /h	l/min	□	Δ
45°	1.0	2.1	0.04	0.67	68	79
	1.5	2.4	0.05	0.83	66	76
	2.0	3	0.06	1.00	49	57
	2.1	3.3	0.06	1.00	42	48
	2.5	3.5	0.06	1.00	41	47
90°	1.0	2.1	0.08	1.33	68	79
	1.5	2.4	0.09	1.50	66	76
	2.0	3	0.11	1.83	49	57
	2.1	3.3	0.11	1.83	42	48
	2.5	3.5	0.12	2.00	41	47
120°	1.0	2.1	0.1	1.67	68	79
	1.5	2.4	0.13	2.17	66	76
	2.0	3	0.15	2.50	49	57
	2.1	3.3	0.15	2.50	42	48
	2.5	3.5	0.17	2.83	41	47
180°	1.0	2.1	0.15	2.50	68	79
	1.5	2.4	0.19	3.17	66	76
	2.0	3	0.22	3.67	49	57
	2.1	3.3	0.23	3.83	42	48
	2.5	3.5	0.25	4.17	41	47
240°	1.0	2.1	0.2	3.33	68	79
	1.5	2.4	0.25	4.17	66	76
	2.0	3	0.29	4.83	49	57
	2.1	3.3	0.3	5.00	42	48
	2.5	3.5	0.33	5.50	41	47
270°	1.0	2.1	0.23	3.83	68	79
	1.5	2.4	0.28	4.67	66	76
	2.0	3	0.33	5.50	49	57
	2.1	3.3	0.34	5.67	42	48
	2.5	3.5	0.37	6.17	41	47
360°	1.0	2.1	0.3	5.00	68	79
	1.5	2.4	0.38	6.33	66	76
	2.0	3	0.44	7.33	49	57
	2.1	3.3	0.45	7.50	42	48
	2.5	3.5	0.5	8.33	41	47



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

12A						
Raza : 3.6m						
Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar	m	m ³ /h	l/min	□	Δ
45°	1.0	2.7	0.05	0.83	53	61
	1.5	3.2	0.06	1.00	47	55
	2.0	3.7	0.07	1.17	42	48
	2.1	4	0.07	1.17	36	42
	2.5	4.2	0.08	1.33	36	42
90°	1.0	2.7	0.1	1.67	53	61
	1.5	3.2	0.12	2.00	47	55
	2.0	3.7	0.14	2.33	42	48
	2.1	4	0.15	2.50	36	42
	2.5	4.2	0.16	2.67	36	42
120°	1.0	2.7	0.13	2.17	53	61
	1.5	3.2	0.16	2.67	47	55
	2.0	3.7	0.19	3.17	42	48
	2.1	4	0.19	3.17	36	42
	2.5	4.2	0.21	3.50	36	42
180°	1.0	2.7	0.19	3.17	53	61
	1.5	3.2	0.24	4.00	47	55
	2.0	3.7	0.28	4.67	42	48
	2.1	4	0.29	4.83	36	42
	2.5	4.2	0.32	5.33	36	42
240°	1.0	2.7	0.26	4.33	53	61
	1.5	3.2	0.32	5.33	47	55
	2.0	3.7	0.38	6.33	42	48
	2.1	4	0.39	6.50	36	42
	2.5	4.2	0.43	7.17	36	42
270°	1.0	2.7	0.29	4.83	53	61
	1.5	3.2	0.36	6.00	47	55
	2.0	3.7	0.43	7.17	42	48
	2.1	4	0.44	7.33	36	42
	2.5	4.2	0.48	8.00	36	42
360°	1.0	2.7	0.39	6.50	53	61
	1.5	3.2	0.49	8.17	47	55
	2.0	3.7	0.57	9.50	42	48
	2.1	4	0.58	9.67	36	42
	2.5	4.2	0.64	10.67	36	42

15A						
Raza : 4.5m						
Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar	m	m ³ /h	l/min	□	Δ
45°	1.0	3.4	0.07	1.17	50	57
	1.5	3.9	0.09	1.50	47	54
	2.0	4.6	0.1	1.67	40	46
	2.1	4.9	0.11	1.83	36	41
	2.5	5.2	0.12	2.00	35	40
90°	1.0	3.4	0.14	2.33	50	57
	1.5	3.9	0.18	3.00	47	54
	2.0	4.6	0.21	3.50	40	46
	2.1	4.9	0.22	3.67	36	41
	2.5	5.2	0.24	4.00	35	40
120°	1.0	3.4	0.19	3.17	50	57
	1.5	3.9	0.24	4.00	47	54
	2.0	4.6	0.28	4.67	40	46
	2.1	4.9	0.29	4.83	36	41
	2.5	5.2	0.32	5.33	35	40
180°	1.0	3.4	0.29	4.83	50	57
	1.5	3.9	0.36	6.00	47	54
	2.0	4.6	0.42	7.00	40	46
	2.1	4.9	0.43	7.17	36	41
	2.5	5.2	0.47	7.83	35	40
240°	1.0	3.4	0.38	6.33	50	57
	1.5	3.9	0.48	8.00	47	54
	2.0	4.6	0.56	9.33	40	46
	2.1	4.9	0.57	9.50	36	41
	2.5	5.2	0.63	10.50	35	40
270°	1.0	3.4	0.43	7.17	50	57
	1.5	3.9	0.54	9.00	47	54
	2.0	4.6	0.63	10.50	40	46
	2.1	4.9	0.65	10.83	36	41
	2.5	5.2	0.71	11.83	35	40
360°	1.0	3.4	0.57	9.50	50	57
	1.5	3.9	0.72	12.00	47	54
	2.0	4.6	0.84	14.00	40	46
	2.1	4.9	0.86	14.33	36	41
	2.5	5.2	0.95	15.83	35	40

S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

17A

Raza : 5m

Unghi	Presiune	Raza	Debit		Precipit. mm/h	
	Bar		m ³ /h	l/min	□	Δ
45°	1.0	4.7	0.09	1.50	33	39
	1.5	4.9	0.12	2.00	38	44
	2.0	5.2	0.14	2.33	40	46
	2.1	5.5	0.14	2.33	37	42
	2.5	5.7	0.15	2.50	38	43
90°	1.0	4.7	0.18	3.00	33	39
	1.5	4.9	0.23	3.83	38	44
	2.0	5.2	0.27	4.50	40	46
	2.1	5.5	0.28	4.67	37	42
	2.5	5.7	0.31	5.17	38	43
120°	1.0	4.7	0.25	4.17	33	39
	1.5	4.9	0.31	5.17	38	44
	2.0	5.2	0.36	6.00	40	46
	2.1	5.5	0.37	6.17	37	42
	2.5	5.7	0.41	6.83	38	43
180°	1.0	4.7	0.37	6.17	33	39
	1.5	4.9	0.46	7.67	38	44
	2.0	5.2	0.54	9.00	40	46
	2.1	5.5	0.56	9.33	37	42
	2.5	5.7	0.61	10.17	38	43
240°	1.0	4.7	0.49	8.17	33	39
	1.5	4.9	0.62	10.33	38	44
	2.0	5.2	0.72	12.00	40	46
	2.1	5.5	0.74	12.33	37	42
	2.5	5.7	0.82	13.67	38	43
270°	1.0	4.7	0.55	9.17	33	39
	1.5	4.9	0.69	11.50	38	44
	2.0	5.2	0.81	13.50	40	46
	2.1	5.5	0.83	13.83	37	42
	2.5	5.7	0.92	15.33	38	43
360°	1.0	4.7	0.74	12.33	33	39
	1.5	4.9	0.92	15.33	38	44
	2.0	5.2	1.08	18.00	40	46
	2.1	5.5	1.11	18.50	37	42
	2.5	5.7	1.22	20.33	38	43

S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

Duze cu udare sub forma dreptunghiulara					
Model	Presiune	Lungime x latime	Debit		
			Bar	m	m ³ /h
LCS515	(duza colt stanga)	1.0	1.2m x 4.2m	0.1	1.67
		1.5	1.2m x 4.3m	0.13	2.17
		2.0	1.5m x 4.5m	0.15	2.50
		2.1	1.5m x 4.5m	0.15	2.50
		2.5	1.5m x 4.5m	0.16	2.67
RCS515	(duza colt dreapta)	1.0	1.2m x 4.2m	0.1	1.67
		1.5	1.2m x 4.3m	0.13	2.17
		2.0	1.5m x 4.5m	0.15	2.50
		2.1	1.5m x 4.5m	0.15	2.50
		2.5	1.5m x 4.5m	0.16	2.67
SS530	(duza centru)	1.0	2.2m x 8.5m	0.21	3.50
		1.5	2.4m x 8.5m	0.25	4.17
		2.0	1.5m x 9m	0.29	4.83
		2.1	1.5m x 9m	0.3	5.00
		2.5	1.5m x 9m	0.33	5.50
ES515	(duza capat)	1.0	1.1m x 4.2m	0.1	1.67
		1.5	1.2m x 4.3m	0.13	2.17
		2.0	1.5m x 4.5m	0.15	2.50
		2.1	1.5m x 4.5m	0.15	2.50
		2.5	1.5m x 4.5m	0.16	2.67
CS530	(duza centru)	1.0	2.2m x 8.5m	0.21	3.50
		1.5	2.4m x 8.5m	0.25	4.17
		2.0	1.5m x 9m	0.29	4.83
		2.1	1.5m x 9m	0.3	5.00
		2.5	1.5m x 9m	0.33	5.50
SS918	(duza centru)	1.0	2.4m x 5.2m	0.27	4.50
		1.5	2.7m x 5.5m	0.33	5.50
		2.0	2.7m x 5.5m	0.38	6.33
		2.1	2.7m x 5.5m	0.39	6.50
		2.5	2.7m x 5.5m	0.43	7.17

S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

Duza cu udare in fascicule S-8A

Raza : 2.4m



Unghi	Presiune Bar	Raza m	Debit		Precipit. mm/h	
			m ³ /h	l/min	o	Δ
90°	1.0	2.1	0.06	1.00	2.28	2.63
	1.5	2.4	0.07	1.17	1.93	2.22
	2.0	2.4	0.08	1.33	2.11	2.43
	2.1	2.4	0.08	1.33	2.29	2.64
	2.5	2.7	0.09	1.50	1.95	2.25
180°	1.0	2.1	0.11	1.83	2.12	2.45
	1.5	2.4	0.14	2.33	1.71	1.98
	2.0	2.4	0.16	2.67	1.8	2.08
	2.1	2.4	0.16	2.67	1.89	2.19
	2.5	2.7	0.18	3.00	1.57	1.81
360°	1.0	2.1	0.23	3.83	2.12	2.45
	1.5	2.4	0.28	4.67	1.67	1.93
	2.0	2.4	0.32	5.33	1.73	2
	2.1	2.4	0.33	5.50	1.77	2.05
	2.5	2.7	0.36	6.00	1.45	1.67

Duza cu udare in fascicule S-16A

Raza : 5.2m

Unghi	Presiune Bar	Raza m	Debit		Precipit. mm/h	
			m ³ /h	l/min	o	Δ
90°	1.0	4.6	0.09	1.50	0.68	0.79
	1.5	4.9	0.1	1.67	0.69	0.8
	2.0	4.9	0.11	1.83	0.75	0.87
	2.1	5.2	0.11	1.83	0.72	0.83
	2.5	5.5	0.12	2.00	0.68	0.78
180°	1.0	4.6	0.16	2.67	0.57	0.66
	1.5	4.9	0.19	3.17	0.6	0.69
	2.0	4.9	0.22	3.67	0.66	0.76
	2.1	5.2	0.23	3.83	0.65	0.75
	2.5	5.5	0.25	4.17	0.62	0.71
360°	1.0	4.6	0.31	5.17	0.51	0.59
	1.5	4.9	0.38	6.33	0.55	0.63
	2.0	4.9	0.44	7.33	0.62	0.72
	2.1	5.2	0.45	7.50	0.61	0.7
	2.5	5.5	0.49	8.17	0.59	0.68

Duza bubbler multi-jet

Unghi	Model	Raza m	Debit	
			m ³ /h	l/min
90°	MSBN-25Q	0.3	0.06	1.00
	MSBN-50Q	0.46	0.11	1.83
180°	MSBN-50H	0.3	0.11	1.83
	MSBN-10H	0.46	0.23	3.83
360°	MSBN-10F	0.3	0.23	3.83
	MSBN-20F	0.46	0.45	7.50

Duza bubbler 5-CST-B

Presiune Bar	Raza m	Debit	
		m ³ /h	l/min
1.0	1.5	0.07	1.17
1.5	1.5	0.07	1.17
2.0	1.5	0.09	1.50
2.1	1.5	0.09	1.50
2.5	1.5	0.1	1.67

Duza bubbler PCB/PCN & AFB



Model	Debit	
	m ³ /h	l/min
25	0.06	1.00
50	0.11	1.83
10	0.23	3.83
20	0.45	7.50



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV
 Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72
 Mobile : +40 723.604.735
 Email: inttech@inttech.ro

MP1000

Raza : 2.5m - 4.5m

Unghi	Presiune Bar	Culoare	Raza m	Debit		Precipit. mm/h	
				m ³ /h	l/min	o	Δ
90°	1.75	Maro = 90° - 210°	--	--	--	--	--
	2		3.7	0.036	0.60	11	12
	2.25		3.8	0.038	0.63	10	12
	2.5		4	0.041	0.68	10	12
	2.75		4.1	0.042	0.70	10	11
	3		4.3	0.044	0.73	10	11
	3.25		4.3	0.045	0.75	10	11
	3.5		4.4	0.047	0.78	10	11
180°	3.75		4.6	0.049	0.82	9	11
	1.75	Albastru deschis = 210° - 270°	--	--	--	--	--
	2		3.7	0.072	1.20	11	12
	2.25		3.8	0.076	1.27	10	12
	2.5		4	0.081	1.35	10	12
	2.75		4.1	0.084	1.40	10	11
	3		4.3	0.088	1.47	10	11
	3.25		4.3	0.091	1.52	10	11
210°	3.5		4.4	0.094	1.57	10	11
	3.75		4.6		0.00	9	11
	1.75	Olive = 360°	--	--	--	--	--
	2		3.7	0.108	1.80	11	12
	2.25		3.8	0.114	1.90	10	12
	2.5		4	0.123	2.05	10	12
	2.75		4.1	0.126	2.10	10	11
	3		4.3	0.132	2.20	10	11
	3.25		4.3	0.135	2.25	10	11
270°	3.5		4.4	0.141	2.35	10	11
	3.75		4.6	0.147	2.45	9	11
	1.75	Albastru deschis = 210° - 270°	--	--	--	--	--
	2		3.7	0.108	1.80	11	12
	2.25		3.8	0.114	1.90	10	12
	2.5		4	0.123	2.05	10	12
	2.75		4.1	0.126	2.10	10	11
	3		4.3	0.132	2.20	10	11
	3.25		4.3	0.135	2.25	10	11
360°	3.5		4.4	0.141	2.35	10	11
	3.75		4.6	0.147	2.45	9	11
	1.75	Olive = 360°	--	--	--	--	--
	2		3.7	0.144	2.40	11	12
	2.25		3.8	0.153	2.55	10	12
	2.5		4	0.161	2.68	10	12
	2.75		4.1	0.169	2.82	10	11
	3		4.3	0.177	2.95	10	11
	3.25		4.3	0.183	3.05	10	11
360°	3.5		4.4	0.19	3.17	10	11
	3.75		4.6	0.195	3.25	9	11



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

MP2000
Raza : 4m - 6.4m

Unghi	Presiune	Culoare	Raza	Debit		Precipit.	
	Bar		m	m ³ /h	l/min	o	Δ
90°	1.75	Negru = 90° - 210°	5.2	0.071	1.18	11	12
	2		5.5	0.074	1.23	10	11
	2.25		5.6	0.08	1.33	10	12
	2.5		5.8	0.086	1.43	10	12
	2.75		6.1	0.091	1.52	10	11
	3		6.4	0.094	1.57	9	11
	3.25		6.6	0.097	1.62	9	10
	3.5		6.7	0.101	1.68	9	10
180°	3.75		6.7	0.106	1.77	9	11
	1.75	Verde = 210° - 270°	5.2	0.133	2.22	11	12
	2		5.5	0.141	2.35	10	11
	2.25		5.6	0.15	2.50	10	12
	2.5		5.8	0.16	2.67	10	12
	2.75		6.1	0.168	2.80	10	11
	3		6.4	0.174	2.90	9	11
	3.25		6.6	0.182	3.03	9	10
	3.5		6.7	0.189	3.15	9	10
210°	3.75		6.7	0.193	3.22	9	11
	1.75	Rosu = 360°	5.2	0.155	2.58	11	12
	2		5.5	0.165	2.75	10	11
	2.25		5.6	0.175	2.92	10	12
	2.5		5.8	0.185	3.08	10	12
	2.75		6.1	0.195	3.25	10	11
	3		6.4	0.205	3.42	9	11
	3.25		6.6	0.214	3.57	9	10
	3.5		6.7	0.222	3.70	9	10
270°	3.75		6.7	0.228	3.80	9	11
	1.75	Negru = 90° - 210°	5.2	0.199	3.32	11	12
	2		5.5	0.212	3.53	10	11
	2.25		5.6	0.225	3.75	10	12
	2.5		5.8	0.238	3.97	10	12
	2.75		6.1	0.249	4.15	10	11
	3		6.4	0.261	4.35	9	11
	3.25		6.6	0.272	4.53	9	10
	3.5		6.7	0.282	4.70	9	10
360°	3.75		6.7	0.293	4.88	9	11
	1.75	Verde = 210° - 270°	5.2	0.265	4.42	11	12
	2		5.5	0.283	4.72	10	11
	2.25		5.6	0.3	5.00	10	12
	2.5		5.8	0.317	5.28	10	12
	2.75		6.1	0.333	5.55	10	11
	3		6.4	0.348	5.80	9	11
	3.25		6.6	0.362	6.03	9	10
	3.5		6.7	0.375	6.25	9	10
360°	3.75		6.7	0.384	6.40	9	11



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV
Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72
Mobile : +40 723.604.735
Email: inttech@inttech.ro

MP3000

Raza : 6.7m - 9.1m

Unghi	Presiune Bar	Culoare	Raza m	Debit		Precipit. mm/h	
				m ³ /h	l/min	o	Δ
90°	1.75	Albastru = 90° - 210°	7.6	0.158	2.63	11	13
	2		8.2	0.166	2.77	10	11
	2.25		8.4	0.175	2.92	10	12
	2.5		8.5	0.185	3.08	10	12
	2.75		9.1	0.195	3.25	9	11
	3		9.1	0.203	3.38	10	11
	3.25		9.1	0.212	3.53	10	12
	3.5		9.1	0.22	3.67	11	12
	3.75		9.1	0.228	3.80	11	13
180°	1.75	Albastru = 90° - 210°	7.6	0.329	5.48	11	13
	2		8.2	0.353	5.88	10	11
	2.25		8.4	0.373	6.22	10	12
	2.5		8.5	0.393	6.55	10	12
	2.75		9.1	0.413	6.88	9	11
	3		9.1	0.431	7.18	10	11
	3.25		9.1	0.449	7.48	10	12
	3.5		9.1	0.466	7.77	11	12
	3.75		9.1	0.481	8.02	11	13
210°	1.75	Galben = 210° - 270°	7.6	0.384	6.40	11	13
	2		8.2	0.411	6.85	10	11
	2.25		8.4	0.436	7.27	10	12
	2.5		8.5	0.459	7.65	10	12
	2.75		9.1	0.481	8.02	9	11
	3		9.1	0.502	8.37	10	11
	3.25		9.1	0.523	8.72	10	12
	3.5		9.1	0.542	9.03	11	12
	3.75		9.1	0.562	9.37	11	13
270°	1.75	Galben = 210° - 270°	7.6	0.501	8.35	11	13
	2		8.2	0.53	8.83	10	11
	2.25		8.4	0.56	9.33	10	12
	2.5		8.5	0.589	9.82	10	12
	2.75		9.1	0.619	10.32	9	11
	3		9.1	0.646	10.77	10	11
	3.25		9.1	0.673	11.22	10	12
	3.5		9.1	0.701	11.68	11	12
	3.75		9.1	0.727	12.12	11	13
360°	1.75	Gri = 360°	7.6	0.659	10.98	11	13
	2		8.2	0.703	11.72	10	11
	2.25		8.4	0.745	12.42	10	12
	2.5		8.5	0.786	13.10	10	12
	2.75		9.1	0.825	13.75	9	11
	3		9.1	0.862	14.37	10	11
	3.25		9.1	0.897	14.95	10	12
	3.5		9.1	0.931	15.52	11	12
	3.75		9.1	0.964	16.07	11	13

MPCorner

MP strip

S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV

Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72

Mobile : +40 723.604.735

Email: inttech@inttech.ro

Raza : 2.5m - 4.5m

Unghi	Presiune Bar	Culoare	Raza m	Debit m ³ /h l/min	
45°	1.75	Turcoaz = 45° - 105°	--	--	--
	2		3.5	0.036	0.60
	2.25		3.8	0.038	0.63
	2.5		4	0.041	0.68
	2.75		4.1	0.042	0.70
	3		4.3	0.044	0.73
	3.25		4.3	0.045	0.75
	3.5		4.4	0.047	0.78
	3.75		4.5	0.049	0.82
90°	1.75		3.2	0.069	--
	2		3.5	0.076	1.27
	2.25		3.8	0.079	1.32
	2.5		4	0.084	1.40
	2.75		4.1	0.086	1.43
	3		4.3	0.094	1.57
	3.25		4.3	0.098	1.63
	3.5		4.4	0.1	1.67
	3.75		4.5	0.104	1.73
105°	1.75		3.2	0.08	--
	2		3.5	0.089	1.48
	2.25		3.8	0.092	1.53
	2.5		4	0.098	1.63
	2.75		4.1	0.102	1.70
	3		4.3	0.11	1.83
	3.25		4.3	0.113	1.88
	3.5		4.4	0.117	1.95
	3.75		4.5	0.12	2.00

Raza : -

Unghi	Presiune Bar	Culoare	Raza m	Debit m ³ /h l/min	
MP Left Strip	2.1	Ivoriu	1.2m x 4.3m	0.0432	0.72
	2.4		1.5m x 4.6m	0.048	0.80
	2.8		1.5m x 4.6m	0.0498	0.83
	3.1		1.5m x 4.6m	0.0522	0.87
	3.4		1.8m x 4.9m	0.057	0.95
	3.8		1.8m x 4.9m	0.0588	0.98
MP Right Strip	2.1	Cupru	1.2m x 4.3m	0.0432	0.72
	2.4		1.5m x 4.6m	0.048	0.80
	2.8		1.5m x 4.6m	0.0498	0.83
	3.1		1.5m x 4.6m	0.0522	0.87
	3.4		1.8m x 4.9m	0.057	0.95
MP Side Strip	3.8		1.8m x 4.9m	0.0588	0.98
	2.1	Maro	1.2m x 8.5m	0.0864	1.44
	2.4		1.5m x 9.1m	0.093	1.55
	2.8		1.5m x 9.1m	0.0996	1.66
	3.1		1.5m x 9.1m	0.1068	1.78
	3.4		1.8m x 9.8m	0.111	1.85
	3.8		1.8m x 9.8m	0.1158	1.93



S.C. INTTECH INDUSTRY SRL

Str. Leonte Filipescu 2, Voluntari / ILFOV
 Phone: +40 21 569.04.17 / Fax: +40 21 230.13.72
 Mobile : +40 723.604.735
 Email: inttech@inttech.ro